

⇒ Consortium



IK4-TEKNIKER (Coordinator)

Polo Tecnológico de Eibar
Calle Iñaki Goenaga, 5
20600 Eibar, Gipuzkoa
SPAIN

Contact person: Javier Barriga
javier.barriga@tekniker.es
www.tekniker.es



ARIES INGENIERÍA Y SISTEMAS, S.A.

Paseo de la Castellana, 130
28046 Madrid
SPAIN

Contact person: Hugo Cachafeiro
hcachafeiro@aries.com.es
www.aries.com.es



CSM Instruments, S.A.

Rue de la Gare, 4
CH - 2034 Pesieux
SWITZERLAND

Contact person: Jiri Nohava
jiri.nohava@csm-instruments.com
www.csm-instruments.com



KEMIJSKI INSTITUT

(National Institute of Chemistry)

Hajdrihova, 19
SI-1000 Ljubljana
SLOVENIA

Contact person: Boris Orel
boris.orel@ki.si
www.ki.si/en



TECNOVAC

TECNOLOGÍA DE VACÍO, S.L.
Avenida Valdelaparra, 27 - Edificio 1, Bajo 3
28108 Alcobendas (Madrid)
SPAIN

Contact person: César Atienza
cesar.atienza@tecnovac.es
www.tecnovac.es



KATHOLIEKE UNIVERSITEIT LEUVEN

Departement MTM KU Leuven
Kasteelpark Arenberg, 44 - bus 2450
B-3001 Leuven (Heverlee)
BELGIUM

Contact person: Jean-Pierre Celis
Jean-Pierre.Celis@mtm.kuleuven.be
www.mtm.kuleuven.be



CENTRALE RECHERCHE, S.A.

Rue Jean Goujon, 8
Paris, 75008
FRANCE

Contact person: Pierre Ponthiaux
www.crsa.ecp.fr



The research leading to these results has received funding from the European Community's Seventh Framework Programme (FP7/2007-2013) under grant agreement n° 310344.



The European Commission total contribution is 1,968,559 € for 36 months. (started March 2013).



NECSO Contact

Coordinator: Javier Barriga
E-mail: javier.barriga@tekniker.es | necso@tekniker.es
Phone: +34 680 656 001

www.necso.eu



Nanoscale Enhanced
Characterisation of Solar
Selective Coatings



→ Concept

The Concentrated Solar Power (CSP) technology based on parabolic trough solar collector for large electricity generation purposes is currently the most mature of all CSP designs. The current parabolic trough design deals with a maximum operating temperature around 400°C in the absorber collector tube, but some recent designs are planned to increase the working temperature to 600°C to increase the performance. These systems are expected to be working during 20-25 years.

However, there is a great lack of knowledge about the performance of the selective absorber coatings of the collectors during the whole life of the receiver.

The main idea behind the NECSO project is to provide tools to the solar plants builders, to guarantee that the selective coating will work properly during 20 to 25 years. Thus, novel experimental methods for testing materials under extreme conditions will be developed in the project and nanoscale characterisation of the nanostructure parameters will be correlated with coating performance. The resulting outcomes are expected to contribute significantly to the infrastructure of the solar energy research, development and industrial activities worldwide.



⇒ Objectives

The two main objectives of the NECSO are:

- 1** To correlate nanoscale structure related requirements (nanoroughness, nanohardness, crystallography, composition, vibrational spectra...) with performance requirements: optical and, more important, life expectancy.
- 2** To develop characterisation and degradation protocols to serve as a powerful tool for coating developers, producers and end users for life prediction to push the collector parameters (temperatures and environments) to higher efficiency parameters.

In order to achieve these main goals the following tasks will be addressed:

Ageing protocol: to analyze the thermal cycling with different gases.

Nanoscale structure and requirements: the composition, nanoroughness and crystallography.

Mechanical properties: Study of the thermal stability, adhesion, nanohardness, and wear.

Degradation analysis by dry and wet corrosion and the possible synergistic impact of vibration.

Optical properties and its evolution.

Limitations to the diffusion after the ageing process.

